

STABILIZER SINGLE PHASE Relay Type



Single Phase Relay Stabilizer



Product specification

Model	DVT-500VA	DVT-1000VA	DVT-1500VA	DVT-2000VA	DVT-3000VA	DVT-5000VA
Rate Capacity	500VA/400Watt	1000VA/800Watt	1500VA/1200Watt	2000VA/1600Watt	3000VA/2400Watt	5000VA/4000Watt
Phase	Single phase					
Input voltage	AC 45-260V, 80-260V, 100-260V, 140-260V (or customized)					
Output voltage	AC 220V or customize					
Frequency	50/60Hz					
Precision	±10% or customized					
Efficiency	>95%					
Control type	Relay type					
Digital display	Show input and output voltage, Load Ratio and Fault Indicator					
Protection	Over temperature, Overvoltage, Undervoltage, Time delay					
Ambient temperature	-10°C~+ 40°C					
Relative Humidity	<95%					
Waveform Distortion	No additional wave form distortion					
Insulating Resistance	Normally more than 2MΩ					
Insulating Class	Class B					
Protection	Overvoltage	Output Voltage $\geq 245V \pm 4V$				
	Low voltage	Output Voltage $\leq 180V \pm 4V$				
	Over temperature	95°C±10°C				
	Delay time	Long time(180 second) / short time(6 second)				
	Undervoltage	Disabled by default, customizable if needed				
Size(mm) L*W*H	157*240*180	157*240*180	157*240*180	220*342*245	220*342*245	220*342*245